



RFID Inlay Breeze Impinj Monza M830

Dimensions (WxH)

42 mm X16 mm (1.638 " X 0.624 ")



DESCRIPTION

Boasting a high-performance read rate, Breeze excels as your RFID inlay of choice in supply chain visibility. With a versatile design that seamlessly integrates into various product types, such as stickers, hangtags and integrated packaging, it's one of the most adaptable inlays in our portfolio. With high detection rates, Breeze can also be deployed for RFID as loss prevention applications in retail, as well as for inventory management.

RFID SPECIFICATIONS

Protocol	ISO/IEC 18000-63:2015 and EPCglobal Gen2v2 compliant and supports Impinj Gen2X
Operating Frequency	860 Mhz - 960 Mhz
Chip Type	Monza M830
Unique TID / UID	96 bits
EPC Memory	128 bits
User Memory	No data
Tag type	UHF

INDUSTRIES

Retail Apparel

Retail Cosmetics

APPLICATIONS



Anti theft



Inventory visibility



Omnichannel



Store processes (Cycle Count / item locator / POS)

ARC CATEGORIES


Spec O

Spec Q

Spec W5

Spec W6

OTHER CERTIFICATIONS




PERFORMANCE

ETSI Read Range	17.80 m
FCC Read Range	9.00 m

READ RANGE

Free Space, Light, & Heavy Loading Conditions



ORIENTATION SENSITIVITY

ETSI

FCC

